



WM97+

Wall Mount Gas Boiler

**WEIL-McLAIN'S WM97+ WALL MOUNT BOILER ...
MAKES THE CHOICE EASY!**

COMPETITIVE WALL MOUNT BOILERS

| "Out of the Box" Standard Features | Basic | Standard | Fire Tube Heat Exchanger | WM97+ | Potential Installation Savings* |
|---|----------------|----------------|--------------------------|-------|---------------------------------|
| Advanced Customizable Control w/LCD Display | | ✓ | ✓ | ✓ | \$100 |
| Built-In Selectable Primary/Secondary Piping | | ✓ | | ✓ | \$200 |
| No Extra Pumps Required for Circuit Lengths Up to 156 ft. and 4 Branches ¹ | | | | ✓ | \$150 |
| Built-in Expansion Tank** | | | | ✓ | \$90 |
| Separate Indirect Tank Supply and Return Connections | ✓ | | | ✓ | \$50 |
| Built-in Low Water Cutoff | | ✓ ² | | ✓ | \$130 |
| 3 Powered System or Zone Circulator Outputs | ✓ ² | ✓ | ✓ ² | ✓ | \$150 |
| 2-Year Residential Parts Warranty | | | ✓ | ✓ | \$100 |

¹See boiler installation manual for system design requirements

²Only some in this category have this item included as standard equipment

*ESTIMATED VALUE AMOUNTS ACTUAL MAY VARY

**70 & 110 models only

MAXIMUM VALUE, PERFORMANCE & EASE

STANDARD EQUIPMENT:

- Three sizes to choose from-70, 110 & 155 MBH - All at 95% AFUE
- Durable stainless steel fire tube heat exchanger design
- Large LCD display control
- Control up to 3 zones and circulators
- Build-in primary/secondary and direct connect piping for any application
- Integrated boiler circulator capable of running circuit up to 156 ft and 4 branches¹
- Outdoor reset control w/included sensor
- Modulating burner-5:1 turndown capable
- Modern sleek boiler jacket design
- Quick maintenance disconnects
- Vent Termination Kit
- Propane Conversion Kit
- System efficiency optimizers:
 - Min/Max On-Time
 - Boost Time
 - Pre/Post Pump Time
- 12-Year heat exchanger warranty
- 2-Year residential parts warranty



**Total Potential
Value of
\$970**

AquaLogic®

WM97+

WEIL-McLAIN



AQUALOGIC



For Optimal Performance

Match the AquaLogic Water Heater with the WM97+ Boiler for abundant domestic hot water production All in one compact footprint!

Saves Time

- Includes all mating piping and electrical connections - makes installation a snap
- Flexible domestic piping connection option (left or right)

Saves Money

- High performance when you need it; maximize savings during low demand periods
- Efficiency levels of a 95%: WM97+ boiler combined with endless on-demand domestic hot water
- Up to four hot water performance mode time periods - for both weekdays and weekends
- A vacation mode for energy savings while you're away from home
- The ability to flow more hot water during peak demand times
- No temperature swings when other faucets/showers are running
- The longevity of a stainless steel tank vs. brazed plate heat exchanger

Product Info:

- Up to 6.1 gallons per minute (DHW)*
- 18.2 gallon 316L stainless steel tank
- 1-1/4" diameter 316L stainless steel coil
- Thermostatic mixing valve
- 3/4" temperature and pressure valve
- Drain valve
- Taco 3 speed circulator (selector switch)
- Two 1" 316L stainless steel flexible connection hoses
- Wire harness and plugs for quick boiler control connection
- Two tank temperature sensors
- Leveling legs

* See product manual for details

