

A white cylindrical water heater tank with a black top and bottom. A brass drain valve is visible on the lower right side. The tank is set against a background of blue water with bubbles. A small label on the tank reads 'WEIL-McLAIN AQUA'.

Built to take the harshest water conditions

The new non-metallic Aqua Pro™ is the right choice to stand up to corrosion.


The Aqua Pro composite tank construction is ideal for all types of water conditions – especially the harshest environments. Check out these additional design features:

- Lightweight, easily maneuvered non-metallic tank
- Available in 4 sizes: 30, 50, 80, and 119 gallons
- No anode to check, no annual maintenance
- Convenient top connections
- Seamless tank construction, no welds
- Digital temperature control
- Removable copper finned high-output coil
- Durable brass drain valve
- Low heat loss, 2" foam insulation



Leverage the power and efficiency of your boiler for domestic hot water with the new Aqua Pro indirect-fired water heater. Flexible to fit a broad range of applications, it's designed to install easily into any system.



Aqua Pro Specs				
 AHRI CERTIFIED™ www.ahridirectory.org	30 Gallon	55 Gallon	80 Gallon	119 Gallon
Ratings				
1st Hour Rating (GPH)	199	217	381	477
Continuous Draw Rating (GPH)	177	177	315	381
Standby Heat Loss (F/HR)	.8	.6	.4	.4
Minimum Heat Output Rate (MBH)	115	115	199	244
Dimensions				
Height to Fitting (in)	40 ½"	41"	53 ½"	74"
Overall Diameter (in)	22 ¾"	28"	28"	28"
Inner Tank Diameter (in)	18"	24"	24"	24"
Approx. Shipping Weight (lbs)	70	95	125	155
Pipe Sizes (MNPT) - All Top Connections	¾"	¾"	DHW 1 ½" Boiler 1"	DHW 1 ½" Boiler 1"



SIMPLIFIED SOLUTIONS FOR OUR COMPLEX WORLD™

WM2009_FLY73_AquaPro