

# Top Reasons to Choose the AquaBalance™

Condensing Heat Only/Combination Gas Boiler

- Durable Stainless Steel Water Tube Heat Exchanger
- High-grade 316L stainless steel with a 316Ti Titanium infused SS shell
- Large diameter series flow water tube insures high velocity to reduce fouling and hot spots
- Low pressure drop, less restrictive than other designs – large diameter water tube produces high flow rates allowing the boiler to provide full power even in high temperature systems
- 10:1 turndown precisely matches minimal energy usage to the immediate system need

#### 2. Highly Efficient & ENERGY STAR® Certified

- Up to 94.4% efficient, the AquaBalance saves fuel
- Exceeds ENERGY STAR<sup>®</sup> requirements
- Eligible for most utility rebates check your local programs
- ASME, AHRI, CSA, Low NOx (SCAQMD) and low lead (NSF61) certified

#### 3. Impressive Domestic Hot Water Production

- Provides up to 4.0 gallons per minute at a 70° F rise\*
- Able to satisfy 2 showers and a faucet/ dishwasher simultaneously (low flow head)\*

# 4. Save Installation Time

- Boiler features a power cord with a 3 prong plug (120V) – simply plug it in
- Prewired for quick connections, 24V thermostat connection box with fuse

# 5. Easy-to-Use Control with LCD Display

- Digital Honeywell boiler control
- Easy to read display with simple status icons

- 6. Designed for Easy Maintenance and Service
- Spacious interior provides room to maneuver, unlike other units
- Planned component placement reduces the need to remove some parts to get to others
- Removable side panels provides full access to all components

## 7. Compact Size – Saves Valuable Floor Space

- Easy to transport, deliver & install (largest size is only 87 lbs.) saving contractors time
- Takes care of 2 functions space heating & Domestic Hot Water – all in one small cabinet\*\*
- 8. Venting Options Accommodate Many Different Structure Styles
- Eases installation with multiple venting options
  sidewall or through-the-roof direct vent
- Capable to vent with PVC, CPVC, PP or SS materials up to 100'
- Boiler's 3-in-1 vent/air adapters readily accepts most approved materials\*\*\*

### 9. Quiet Operation

• Heavy gauge insulated jacket provides whisper quiet operation and comfort

### 10. Backed by Weil-McLain

- Industry leader since 1881
- Rigorous standards for quality
- Unrivaled factory technical and field sales support

\*155MBH combi unit

```
**Combi version only
```

\*\*\*Additional adapter required for Centrotherm PP

