WM WEIL-McLAIN

MARKETING BULLETIN

BULLETIN NO: MB-1218 DATE: October 17, 2012 PAGE: 1 of 1

TO:	All Weil-McLain Distributors and Agents
FROM:	John Kopf – Sr. Commercial Product Manager

SUBJECT: Discontinuation of PFG Boiler Line

The DOE has published a final ruling on minimum efficiency levels for commercial boilers. According to this document, any boiler manufactured on or after March 2, 2012 and intended for sale in the U.S. must meet the requirements in Table 1 from 10 CFR 431.87, as shown below:

	Gas Fired				Oil Fired		
Boiler Type	Water	Water	Steam (except natural draft)	Steam (natural draft)	Water	Water	Steam
Input	≥300,000 Btu/hr ≤2,500,000 BTU/hr	>2,500,000 BTU/hr	≥300,000 BTU/hr	≥300,00 BTU/hr	≥300,000 Btu/hr ≤2,500,000 BTU/hr	>2,500,000 BTU/hr	≥300,00 BTU/hr
New Minimum Efficiency	80% thermal	82% combustion	79% thermal	77% thermal	82% thermal	84% combustion	81% thermal

PFG boilers

Based on this DOE requirement we are discontinuing manufacturing of our PFG Commercial Gas Boiler line effective immediately. This product will be shown in the discontinued portion of the AHRI listing and will be available for sale until all existing inventories are depleted. We will continue providing technical support, parts replacement and service for the PFG line as long as deemed necessary.

We will continue accepting orders for the PFG boilers on a first come basis. Please contact Weil-McLain customer service for PFG availability.

If you have any questions, please contact your local Weil-McLain sales representative.

Thank you for your continued support of Weil-McLain products and services.