SCHEMATIC WIRING DIAGRAM PILOT THERMOCOUPLE TERMINAL BLOCK ON THERMOCOUPLE LEAD WIRE NUT-GAS VALVE SERVICE SWITCH TRANSFORMER (BY OTHERS) EQUIPMENT GROUND LOW WATER 0 CUT-OFF (WHEN USED) THERMOSTAT (NOTE 5) PLUG-IN DEST RELAY OPERATING FIXED HIGH LIMIT LIMIT CIRCULATOR (NOTE 6)

ELECTRICAL SHOCK HAZARD, CAN CAUSE SEVERE INJURY OR DEATH. DISCONNECT POWER BEFORE INSTALLING AND/OR SERVICING.

WARNING

1. ALL WIRING MUST BE INSTALLED IN ACCORDANCE WITH:

U.S.A. - NATIONAL ELECTRICAL CODE AND ANY OTHER NATIONAL. STATE, OR LOCAL CODE REQUIREMENTS HAVING JURISDICTION.

CANADA - C.S.A. C22.1 CANADIAN ELECTRICAL CODE PART 1 AND ANY OTHER NATIONAL PROVINCIAL OR LOCAL CODE REQUIREMENTS HAVING JURISDICTION.

2. ALL SAFETY CIRCUIT WIRING MUST BE: U.S.A. - N.E.C. CLASS 1.

CANADA - C.S.A. C22.1 C.E.C. PART 1.


3. IF ORIGINAL WIRE AS SUPPLIED WITH THE APPLIANCE MUST BE REPLACED, TYPE 90'C OR ITS EQUIVALENT MUST BE USED.

INSTRUCTIONS FOR APPLICATION, WIRING AND THERMOSTAT ANTICIPATOR SETTING.

4. REFER TO CONTROL COMPONENT INSTRUCTIONS PACKED WITH BOILER FOR APPLICATION INFORMATION. 5. FOR SINGLE ZONE SYSTEMS, THERMOSTAT ANTICIPATOR SETTING IS 0.40 AMPS. FOR MULTIPLE ZONE SYSTEMS USING ZONE VALVES OR CIRCULATORS. REFER TO COMPONENT MANUFACTURER'S

6. CIRCULATOR NOT USED WITH ECH GRAVITY HOT WATER SYSTEMS.

LADDER WIRING DIAGRAM



HIGH VOLTAGE LOW VOLTAGE

NOTICE - ALL CONTACTS SHOWN WITHOUT POWER APPLIED - OFF SHELF CONDITION.

Wiring Diagram for EGH-85 and 95, PFG-6 and 7

 Standing Pilot, 24 Volt • Single Seat Gas Valve w/Dual Limit Control

· Forced Hot Water or Gravity Hot Water.

Without Tankless Heater

WEIL-McLAIN A United Dominion Company

Well-McLain . 500 Blaine St. . Michigan City, IN 46360-2388

PART NUMBER 550-224-061/1290WM